



**BOSSPLOW.COM**

See how BOSS continues to BACK YOU UP.  
Get more info, watch videos, find a dealer or chat live.

Call 800-286-4155  
Email [sales@bossplow.com](mailto:sales@bossplow.com)



Ask your dealer or visit [bossplow.com](http://bossplow.com) to explore the complete lineup of BOSS products, including Truck Equipment, ATV/UTV Equipment, Heavy Equipment, Ice Control Equipment and Accessories.



Exclusive to BOSS Owners, joining this community gives you a profile page, a free gift and access to special offers and information on BOSS products and services.



SnowCare for Troops is a nationwide outreach program that performs free snow removal for the families of men and women serving overseas and disabled veterans.



**BOSS PRODUCTS**  
**2010 THE BOSS WAY**  
**P.O. BOX 787**  
**IRON MOUNTAIN, MI 49801-0787**

BOSS SNOWPLOW PRODUCTS  
ARE DESIGNED AND MANUFACTURED IN  
AN APPROVED ISO 9001:2008  
REGISTERED FACILITY.

Patents: [www.ttcopats.com](http://www.ttcopats.com)  
©2017 BOSS PRODUCTS. ALL RIGHTS RESERVED.  
PRINTED IN U.S.A. FORM #450B-2017 (UPDATED 7/17)

Hardox is a registered trademark of SSAB Technology. The "T" logo is a registered trademark/service mark of Facebook, Inc. The Twitter logo is a registered trademark/service mark of Twitter, Inc. The YouTube logo is a registered trademark/service mark of Google Inc. The Google+ logo is a service mark of Google Inc. The "in" logo is a registered service mark of LinkedIn Corporation. The Instagram logo is a registered trademark/service mark of Instagram, LLC. The Blogger logo is a registered service mark of Google Inc. The National IPA logo is a service mark of the National Intergovernmental Purchasing Alliance Company. The Advantage International Registrar logo is a trademark of Advantage International Registrar, Inc. All other trademarks belong to BOSS Snowplow.



# TRUCK EQUIPMENT 2017

SNOWPLOWS & SPREADERS







2

3

Everything we do at BOSS comes back to one goal: giving snow and ice removal professionals everything they need to RESTORE ORDER when winter weather brings chaos. That’s why we never stop pushing our designs, engineering and innovations to help make your job easier and more productive. Because at BOSS, our promise is that we will always be there to BACK YOU UP.

BOSS Products, a division of The Toro Company, reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.

# TABLE OF CONTENTS

|    |                  |    |                      |    |                        |
|----|------------------|----|----------------------|----|------------------------|
| 4  | BOSS Innovations | 14 | Standard-Duty        | 24 | Forge Hopper Spreader  |
| 6  | DXT              | 16 | Super-Duty           | 26 | TGS Tailgate Spreaders |
| 8  | XT               | 18 | Trip-Edge            | 28 | Accessories            |
| 10 | EXT              | 20 | Heavy-Duty           | 34 | Specifications         |
| 12 | HTX              | 22 | VBX Hopper Spreaders |    |                        |



# INNOVATING FOR THE WAY YOU WORK

When winter is at its worst, the job calls for more than muscle, which is why BOSS engineers smart, tough, innovative solutions to make snow and ice removal fast, easy and efficient. With a variety of snow and ice control technologies and features to make your job more productive, BOSS has what today's professionals need to take on winter and RESTORE ORDER.



\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.

LEARN MORE ABOUT BOSS PRODUCTS  
**BOSSPLOW.COM**

## PRO-LID

Weather-sealed, polyethylene hard cover protects deicing material inside the VBX Spreader. The BOSS Pro-Lid can be opened while remaining on the ground with most vehicles. (Available as an accessory on VBX Spreaders: VBX 6500, VBX 8000 and VBX 9000 only.)



## PRE-WET

Allows contractors to pre-wet solid deicing materials, improving the efficiency of solid deicing materials. Equipped with a 60-gallon tank capacity, this system is available as an option on all new VBX and Forge Spreaders.



## A NEW ERA IN PLOW LIGHTING

Plow in a whole new light with best-in-class 100% LED lighting, integrated with Ice Shield Technology™ to prevent snow and ice build-up on the lens. Comes standard on all BOSS truck plows.




## ATTACH WITH EASE

Attach your plow in just three easy steps with the easy to use SmartHitch® 2 attachment system.



## SUPERIOR CONTROL OPTIONS

Our high-tech, ergonomic controls feature large, backlit buttons for ease of use.



D-Force maintains consistent hydraulic down force through the use of a hydraulic accumulator to improve scraping performance while backdragging. D-Force is an optional accessory on new truck plow purchases. Available for select Straight-Blade truck plow models including Super-Duty and HTX Straight-Blade plows. (Excludes EXT, Heavy-Duty and Trip-Edge plows.)



## BACKDRAG EDGES

Available accessory on Straight-Blade plows. (Excludes 9' and 10' Heavy-Duty, Trip-Edge and EXT plows.) Complementary accessory to D-Force, backdrag edges improve scraping performance when backdragging.



## FLEET-FLEXIBLE UNDERCARRIAGE

The enhanced fleet flexibility comes from the RT3 Undercarriage, allowing you to quickly and easily swap between snowplows in your BOSS fleet.





DXT

## FULLY FEATURED AND FULLY TOUGH

The durable, fully featured BOSS DXTs are the ultimate tools to fight all things snow and ice. Dual-trip design enhances plow protection when striking obstacles in any position. Flared wings with an enhanced curl throw snow with maximum efficiency and the DXT's multi-position plow blade can quickly and easily switch positions to move large amounts of snow. The smooth running DXT is state of the art for plowing protection and performance.

### STANDARD FEATURES:

- Steel 8'2", 9'2", 10' Poly 8'2", 9'2"
- Stainless Steel 8'2", 9'2"

- **Patented Dual-Trip Design** for enhanced plow protection when striking hidden obstacles in any position.
- **SmartLight™ 3** uses 100% LED lights with an 8-10 year life expectancy and Ice Shield Technology™ to prevent snow and ice build-up.
- **Chainless Hydraulic Cylinder Lifting System** greatly reduces bounce during transport and provides full float capability.
- **½" x 6" Long-Lasting, Durable Base Angle** to provide extended wear resistance and comes with built-in curb guards and patented snow catcher.
- **Flared Wings** with enhanced curl to throw snow with maximum efficiency.
- **Patented Snow Catcher** is designed to catch snow at the plow's pivot point, so no snow lines are left behind.
- **Reinforced Moldboard** increases blade rigidity for increased durability.
- **Heavy-Duty Push Frame and Center Section** for additional strength and reliability.
- **High-Performance Hydraulic Package** delivers reliability and speed.
- **Enclosed Hydraulics** protects against corrosion and hydraulic freeze-up.
- **SmartLock® Cylinders** lock blades in place when backdragging.

▶ SEE IT IN ACTION  
**BOSSPLOW.COM**

**SL3**  
LED TECHNOLOGY  
with  
Ice Shield Technology™

- Nearly double the light output of standard halogen systems.
- Life expectancy of 8 to 10 years.
- Ice Shield Technology™ heats the lens to prevent ice build-up.
- Standard on all BOSS truck plows.

9'2" Steel DXT – Also available  
in Poly and Stainless Steel



\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.

**SL3**  
LED TECHNOLOGY  
with  
Ice Shield Technology™

**BOSS**  
*Smart Hitch 2*

**BOSS**  
*Smart Touch 2*

**Smart Shield**  
BOSS



Patented Dual-Trip Design combines Trip-Edge and Full Moldboard Trip technologies on every DXT plow for protection from obstacles in any position, high or low.



XT

## PERFORMANCE IN EVERY PUSH

The BOSS XT is built to perform with innovative flared blade wings and an enhanced curl design that throws snow higher and farther than conventional plows. The superslick polyethylene surface of the PolyXT keeps snow from sticking. The durable steel plows feature a baked-on powder-coat paint finish with exclusive zinc primer to resist corrosion and outlast the elements. The BOSS XT is just another innovation helping you to RESTORE ORDER.

Steel 7'6", 8'2", 9'2"  
Poly 8'2", 9'2"

### STANDARD FEATURES:

QUESTIONS? CHAT LIVE ONLINE.  
**BOSSPLOW.COM**

- > **Full Moldboard Trip Design** helps to prevent plow damage when an obstacle is encountered.
- > **SmartLight™ 3** uses 100% LED lights with an 8-10 year life expectancy and Ice Shield Technology™ to prevent snow and ice build-up.
- > **Chainless Hydraulic Cylinder Lifting System** greatly reduces bounce during transport and provides full float capability.
- > **½" x 6" Cutting Edge** built using Hardox® wear plate to provide extended wear resistance and comes with built-in curb guards and patented snow catcher.
- > **Patented Snow Catcher** is designed to catch snow at the plow's pivot point, so no snow lines are left behind.
- > **Reinforced Moldboard** increases blade rigidity for increased durability.
- > **Heavy-Duty Push Frame and Center Section** for additional strength and reliability.
- > **High-Performance Hydraulic Package** delivers reliability and speed.
- > **SmartLock® Cylinders** lock blades in place when backdragging.
- > **Enclosed Hydraulics** protects against corrosion and hydraulic freeze-up.

8'2" Poly XT – Also available in Steel

\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.

**HARDOX®**  
WEAR PLATE

Hardox® cutting edge guarantees outstanding resistance to impact and extreme abrasion while delivering maximum service life and enhanced productivity.

**SL3**  
LEA TECHNOLOGY  
with Ice Shield Technology™

**BOSS**  
*Smart Hitch 2*

**BOSS**  
*Smart Touch 2*

**SmartShield**  
BOSS

**2**  
YEAR WARRANTY



EXT

## EXPAND PARKING LOT PRODUCTIVITY

The EXT is a popular, new innovation from BOSS, with expandable wings that enhance productivity and efficiency to put winter in its place. It plows at 8 feet for tighter cuts and expands to 10 feet with pitched-forward wings for optimal productivity, making it the perfect parking lot plow. The EXT is a versatile and flexible addition to your fleet and another powerful tool in your plowing arsenal that's built to BACK YOU UP.

### STANDARD FEATURES:

> Steel 8' Retracted, 10' Expanded with Pitched-Forward Wings

- > **Expandable, Fully Hydraulic, Pitched-Forward Wings** let you quickly and easily expand from 8' to 10' in width. A true 10' width combined with pitched-forward wings let the EXT take wider passes, carrying and moving more snow more efficiently.
- > **SmartLight™ 3** uses 100% LED lights with an 8-10 year life expectancy and Ice Shield Technology™ to prevent snow and ice build-up.
- > **Chainless Hydraulic Cylinder Lifting System** greatly reduces bounce during transport and provides full float capability.
- > **Standing Tall and Strong** at 30 inches high with 9 vertical ribs, the EXT moves a high volume of snow with resilience.

- > **Reinforced Moldboard** increases blade rigidity for increased durability.
- > **Heavy-Duty Push Frame and Push Frame Attachment Bar** for additional strength and reliability.
- > **High-Performance Hydraulic Package** delivers reliability and speed.
- > **Enclosed Hydraulics** protects against corrosion and hydraulic freeze-up.

SEE HOW BOSS BACKS YOU UP.  
[BOSSPLOW.COM](http://BOSSPLOW.COM)




\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.

**SL3**  
ICE SHIELD TECHNOLOGY™

**BOSS**  
*Smart Hitch 2*

**BOSS**  
*Smart Touch 2*

**Smart Shield**  
BOSS





HTX

# FOR LIGHTER-DUTY TRUCKS WITH HEAVY WORKLOADS

Our full line of HTX plows brings all the power and innovation of BOSS full-size V-plows and Straight-Blades to your light-duty truck. With today's business owner and homeowner in mind, BOSS has engineered the HTX line for today's lighter-duty and half-ton trucks by putting just the right amount of steel in exactly the right place for the best combination of strength and weight. The precisely crafted, ultra-efficient HTX line is built to handle winter. Because when you need to RESTORE ORDER with your lighter-duty truck, BOSS is always there to BACK YOU UP.

12

\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.

GET HELP SELECTING THE RIGHT BOSS PLOW FOR YOUR TRUCK.  
**BOSSPLOW.COM**

D-Force maintains consistent hydraulic down force through the use of a hydraulic accumulator to improve scraping performance while backdragging. D-Force is an optional accessory on new truck plow purchases. Available for select Straight-Blade truck plow models including Super-Duty and HTX Straight-Blade plows. (Excludes EXT, Heavy-Duty and Trip-Edge plows.)



7'6"  
V-Plow Steel

7', 7'6"  
Poly

7', 7'6"  
Steel

7', 7'6"  
Stainless Steel

13

- Steel V-Plow 7'6"  
Poly, Steel Straight-Blade 7', 7'6"
- Stainless Steel Straight-Blade 7', 7'6"

## STANDARD FEATURES:

- > **Full Moldboard Trip Design** helps to prevent plow damage when an obstacle is encountered.
- > **SmartLight™ 3** uses 100% LED lights with an 8-10 year life expectancy and Ice Shield Technology™ to prevent snow and ice build-up.
- > **Chainless Hydraulic Cylinder Lifting System** greatly reduces bounce during transport and provides full float capability.
- > **Strong, Durable Push Frame and Attachment Bar** designed for additional strength and reliability.
- > **High-Performance Hydraulic Package** delivers reliability and speed.
- > **Enclosed Hydraulics** protects against corrosion and hydraulic freeze-up.





STANDARD-DUTY

## THE TRIED AND TRUSTED STRAIGHT-BLADE

BOSS Standard-Duty Straight-Blade Plows get the job done right. A baked-on powder-coat paint finish with zinc primer resists corrosion. Heavy-duty push frame and push frame attachment bar, optimized blade curl and reinforced moldboard are standard on every BOSS Straight-Blade. These plows RESTORE ORDER with unsurpassed reliability and strength. The BOSS Standard-Duty is a tried, trusted, powerful tool from BOSS that's built to BACK YOU UP.

### STANDARD FEATURES:


> Steel 7'6"

- > **Full Moldboard Trip Design** helps to prevent plow damage when an obstacle is encountered.
- > **SmartLight™ 3** uses 100% LED lights with an 8-10 year life expectancy and Ice Shield Technology™ to prevent snow and ice build-up.
- > **Chainless Hydraulic Cylinder Lifting System** greatly reduces bounce during transport and provides full float capability.
- > **Cast-Iron Plow Shoes** provide extended wear resistance compared to steel shoes.
- > **Blade Shock Absorber** stabilizes and cushions the trip action.
- > **Heavy-Duty Push Frame and Attachment Bar** for additional strength and reliability.
- > **High-Performance Hydraulic Package** delivers reliability and speed.
- > **Enclosed Hydraulics** protects against corrosion and hydraulic freeze-up.



LEARN MORE ABOUT BOSS PRODUCTS  
[BOSSPLOW.COM](http://BOSSPLOW.COM)

7'6" Standard-Duty



D-Force maintains consistent hydraulic down force through the use of a hydraulic accumulator to improve scraping performance while backdragging. D-Force is an optional accessory on new truck plow purchases. Available for select Straight-Blade truck plow models including Super-Duty and HTX Straight-Blade plows. (Excludes EXT, Heavy-Duty and Trip-Edge plows.)



\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.





# A BIGGER TAKE ON A CLASSIC

The bigger jobs call for the BOSS Super-Duty Straight-Blade. The durable steel blade features a baked-on powder-coat paint finish with zinc primer to resist corrosion, and the superslick polyethylene moldboard of the poly blade prevents snow from sticking. The Super-Duty has everything you love about BOSS Straight-Blades with extra strength, making it a monster when it's time to RESTORE ORDER. It's another powerful tool from BOSS that's built to BACK YOU UP.

- Steel 7'6", 8', 8'6", 9'
- Poly 7'6", 8'

## STANDARD FEATURES:

SEE IT IN ACTION  
[BOSSPLOW.COM](http://BOSSPLOW.COM)

- > **Full Moldboard Trip Design** helps to prevent plow damage when an obstacle is encountered.
- > **SmartLight™ 3** uses 100% LED lights with an 8-10 year life expectancy and Ice Shield Technology™ to prevent snow and ice build-up.
- > **Chainless Hydraulic Cylinder Lifting System** greatly reduces bounce during transport and provides full float capability.
- > **Cast-Iron Plow Shoes** provide extended wear resistance compared to steel shoes.
- > **Blade Shock Absorber** stabilizes and cushions the trip action.
- > **Reinforced Moldboard** increases blade rigidity for increased durability.
- > **Heavy-Duty Push Frame and Attachment Bar** for additional strength and reliability.
- > **High-Performance Hydraulic Package** delivers reliability and speed.
- > **Enclosed Hydraulics** protects against corrosion and hydraulic freeze-up.

\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.

D-Force maintains consistent hydraulic down force through the use of a hydraulic accumulator to improve scraping performance while backdragging. D-Force is an optional accessory on new truck plow purchases. Available for select Straight-Blade truck plow models including Super-Duty and HTX Straight-Blade plows. (Excludes EXT, Heavy-Duty and Trip-Edge plows.)



8' Steel Super-Duty





# ROLL WITH WINTER'S PUNCHES

BOSS Trip-Edge Snowplows are engineered to power through the heaviest snow and any obstacles that come with it. The extra-rigid moldboard and trip-edge technology ensure that only the cutting edge trips when you hit an obstacle, so you won't lose the load you're pushing. Trip-Edge Snowplows feature four adjustable trip return springs, so you can customize the trip spring tension for the job at hand. Available in steel and stainless steel for pickup truck applications, BOSS Trip-Edge Snowplows are built to BACK YOU UP.

STANDARD FEATURES:

- Steel 7'6", 8', 9'
- Stainless Steel 8', 9'

- > **Trip-Edge Design** helps to prevent plow damage when an obstacle is encountered.
- > **SmartLight™ 3** uses 100% LED lights with an 8-10 year life expectancy and Ice Shield Technology™ to prevent snow and ice build-up.
- > **Chainless Hydraulic Cylinder Lifting System** greatly reduces bounce during transport and provides full float capability.
- > **Adjustable Trip Springs** allow you to customize the trip spring tension.
- > **Cast-Iron Plow Shoes** provide extended wear resistance compared to steel shoes.
- > **Reinforced Moldboard** increases blade rigidity for increased durability.
- > **Heavy-Duty Push Frame and Attachment Bar** for additional strength and reliability.
- > **Enclosed Hydraulics** protects against corrosion and hydraulic freeze-up.

QUESTIONS? CHAT LIVE ONLINE.  
[BOSSPLOW.COM](http://BOSSPLOW.COM)

Adjustable Trip Springs

Trip-Edge

\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.





# WHEN WINTER HITS HARD, HIT BACK HARDER

If you're looking for larger, heavy-duty plows, BOSS has what you want. Designed for medium-duty trucks, the BOSS Heavy-Duty Straight-Blades feature a reinforced moldboard with enhanced blade curl to power through deep, wet snow. The versatility of the dual-trip BOSS DXT allows you to scoop, stack and punch through hard-packed banks with power and performance. Both models come standard with the SL3 light system with Ice Shield Technology™ to handle every job, even in the worst conditions. Because when it's on you to RESTORE ORDER, BOSS is always there to BACK YOU UP.

Steel Heavy-Duty 9', 10'  
Steel DXT 10'

STANDARD FEATURES:

- > **Patented Dual-Trip Technology** on the DXT combines trip-edge and full moldboard trip technology to maximize impact protection.
- > **SmartLight™ 3** uses 100% LED lights with an 8-10 year life expectancy and Ice Shield Technology™ to prevent snow and ice build-up.
- > **Chainless Hydraulic Cylinder Lifting System** greatly reduces bounce during transport and provides full float capability.
- > **½" x 6" Long-Lasting, Durable Base Angle** to provide extended wear resistance and comes with built-in curb guards and patented snow catcher (DXT only).
- > **Cast-Iron Plow Shoes** provide extended wear resistance compared to steel shoes (optional on 10' DXT).
- > **Full Moldboard Trip Design** helps to prevent plow damage when an obstacle is encountered (Straight-Blade only).
- > **Dual Shock Absorbers** stabilize and cushion the trip action (Straight-Blade only).
- > **Heavy-Duty Push Frame and Attachment Bar (Heavy-Duty) and Center Section (DXT)** designed for additional strength and reliability.
- > **Reinforced Moldboard** increases blade rigidity for increased durability.
- > **High-Performance Hydraulic Package** delivers reliability and speed.
- > **Enclosed Hydraulics** protects against corrosion and hydraulic freeze-up.

SEE HOW BOSS BACKS YOU UP.  
[BOSSPLOW.COM](http://BOSSPLOW.COM)

\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.



10' Heavy-Duty  
Straight-Blade Steel

10' DXT Steel





## VBX HOPPER SPREADERS

# MAXIMUM EFFICIENCY, SPEED AND PRECISION

BOSS Hopper Spreaders are some of the most powerful tools in your snow and ice removal arsenal. Our fast-growing family of VBX Spreaders are fully featured for ease of use and maximum productivity for years of operation in harsh winter conditions. The VBX family features models with both pintle and auger feeds, powerful electric motors, standard worklights, easy to use controls and the flexibility to spread a variety of deicing materials. BOSS builds quality and durability into every spreader, helping you to RESTORE ORDER.

### STANDARD FEATURES:

> VBX 6500, VBX 8000, VBX 9000

- > **Pintle Chain or Auger Feed System** features either a heavy-duty pintle chain or mild steel helical auger for long life and reliability.
- > **Poly Hopper** is built to outlast the elements.
- > **Dual Variable Speed Controller** is equipped with auto-reverse (auger only) and over-load protection.
- > **LCD Screen In-Cab Controller** is backlit for clear visibility and ease of use.
- > **14.5" Diameter Urethane Spinner** is durable, corrosion-resistant and ensures consistent distribution.
- > **Enclosed Spinner Motor** is weather and dust sealed to ensure performance, durability and reliability.
- > **Tarp With Integral Tie-Downs** to protect spreading material from the elements.
- > **Dual Variable Speed Vibrators** prevent material bridging for ease of operation (standard for auger; available as an accessory for pintle).

- > **Inverted V-Baffle** reduces material build-up for optimal spreading efficiency (standard for auger; available as an accessory for pintle).
- > **Chain Cleaning Brush** removes excess material from chain on every pass (pintle chain only).
- > **Full-Length Slide-Out Tray** captures falling deicing material, keeping it away from truck bed, preventing corrosion (pintle chain only).

### ADDITIONAL ACCESSORIES

- > **Pre-Wet** allows contractors to pre-wet solid deicing materials, improving material efficiency. (Available accessory on new VBX Spreaders.)
- > **Pro-Lid** weather-sealed, polyethylene hard cover protects deicing materials. (Available accessory for VBX Spreaders.)

### PRO-LID

Weather-sealed, polyethylene hard cover protects deicing material inside the VBX Spreader. The BOSS Pro-Lid can be opened while remaining on the ground with most vehicles. (Available as an accessory on VBX Spreaders: VBX 6500, VBX 8000 and VBX 9000 only.)

22

23

**VBX 6500**  
1.5 cubic yards of capacity



**VBX 8000**  
2 cubic yards of capacity



**VBX 9000**  
3 cubic yards of capacity

\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.



# FIGHT ICE WITH STEEL

Introducing the BOSS Forge, a stainless steel Hopper Spreader from BOSS. It performs just as powerfully and reliably as the VBX Spreader line while offering a fully stainless steel hopper. The Forge is constructed using a combination of bolting, riveting and welding for optimal durability and serviceability throughout the spreader's lifetime. The stainless steel BOSS Forge is available with either a pintle chain or auger feed system. Both the hopper and the drive train housing are constructed with one of the heaviest-gauge materials in the market, enhancing the Forge's sturdiness and durability in adverse winter conditions. It's another example of a tough, reliable innovation from BOSS that is built to BACK YOU UP.

> Forge 2.0

## STANDARD FEATURES:

- > **Pintle Chain or Auger Feed System** features either a heavy-duty pintle chain or mild steel helical auger for long life and reliability.
- > **Chain Cleaning Brush** removes excess material from chain on every pass (pintle chain only).
- > **Stainless Steel Hopper** is built to outlast the elements.
- > **14.5" Diameter Urethane Spinner** is durable, corrosion-resistant and ensures consistent distribution.
- > **Enclosed Spinner Motor** is weather and dust sealed to ensure performance, durability and reliability.
- > **Vibrator** prevents material bridging for ease of operation (auger only).
- > **Inverted V-Baffle** reduces material build-up for optimal spreading efficiency (auger only).
- > **Full-Length Slide-Out Tray** captures falling deicing material, keeping it away from truck bed, preventing corrosion (pintle chain only).
- > **Dual Variable Speed Controller** is equipped with auto-reverse and over-load protection and is backlit for clear visibility and ease of use.

## ADDITIONAL ACCESSORIES

- > **Pre-Wet** allows contractors to pre-wet solid deicing materials, improving material efficiency.
- > **For additional accessories, including the Forge light kit, tarp, vibrator, inverted V (pintle) and more, ask your BOSS Dealer.**

\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.

## PRE-WET

Allows contractors to pre-wet solid deicing materials, improving the efficiency of solid deicing materials. Equipped with a 60-gallon tank capacity, this system is available as an option on all new VBX and Forge Spreaders.



FORGE 2.0  
2 cubic yards of capacity

LEARN MORE ABOUT BOSS PRODUCTS  
[BOSSPLOW.COM](http://BOSSPLOW.COM)





## TGS TAILGATE SPREADERS

# GET THE JOB DONE RIGHT, FAST

The TGS Spreader series from BOSS is the easiest way to arm yourself against all things snow and ice. BOSS tailgate-mounted spreaders attach easily and disperse deicing materials quickly and efficiently to make your job as smooth and steady as possible. All TGS Spreaders are built tough to handle harsh conditions, because BOSS knows the faster you can RESTORE ORDER to your community, the better.

### STANDARD FEATURES:

> TGS 300, TGS 600, TGS 800, TGS 1100

- > **Adjustable Feed Gate** allows you to adjust the material discharge amount (optional on TGS 300).
- > **Poly Adjustable Material Deflector** allows you to adjust the material discharge width and direction pattern.
- > **12" Diameter Urethane Spinner** is durable, corrosion-resistant and ensures consistent distribution.
- > **Enclosed 12-Volt Electric High-Torque Motor** is weather and dust sealed to ensure performance, durability and reliability.
- > **Low-Profile Poly Hopper Design** provides better visibility.
- > **Variable Speed Control** equipped with blast feature and overload protection.
- > **Choose Your Attachment System** with a slide-in system or the RT3 system. (RT3 not available on TGS 300.)

- > **Solid Poly Hopper Cover** protects against weather and is made to last.
- > **Stabilizer Arms and Tie-Down Straps** minimize any side-to-side movement. (Stabilizer arms not available on TGS 300.)
- > **Top Screen With Bag Splitter** easily opens bags and filters deicing material. (Bag splitter not included on TGS 300.)
- > **Enclosed Feed Motor** powers the Feed Paddle Mechanism with 12 volts of high-torque electric power (TGS 800 only).
- > **Swing-Away Spinner Assembly** allows for quick removal of leftover material (TGS 800 only).
- > **Material Saver System** eliminates material flow when spreader is not in use. (Standard on TGS 300. Optional on the TGS 600 and TGS 1100, not available on TGS 800. Only needed for select materials.)
- > **For Optional Accessories, Ask Your BOSS Dealer.**

The selection of proper deicing materials can be complicated and varies by personal preference, experience and environmental concerns. All factors should be considered before making your selection.

SEE IT IN ACTION  
BOSSPLOW.COM



The BOSS TGS series works with a variety of deicing materials to fit the job at hand. See the Spreader Materials Guide on Page 32 to learn more.



TGS 1100 has a capacity of 11 cubic feet, or 800 lb.

TGS 800 has a capacity of 8 cubic feet, or 780 lb.

TGS 600 has a capacity of 6 cubic feet, or 400 lb.

TGS 300 has a capacity of 3 cubic feet, or 200 lb.

\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.

**Optional RT3 Attachment System** allows you to easily attach and detach your spreader (not available on TGS 300).





# BOSS SNOWPLOW AUTHORIZED ACCESSORIES

## CONTROL OPTIONS



Mount it on your dash  
(with or without handle).



Attach it to a  
pedestal mount.

## MOUNTING OPTIONS

Attach the versatile SmartTouch® 2 Handheld Control to a pedestal mount or mount it on your dash (with or without handle).

|                       |          |
|-----------------------|----------|
| PEDESTAL MOUNT .....  | MSC09658 |
| DASHBOARD MOUNT ..... | MSC09660 |

## D-FORCE CONTROLLER

The new D-Force controller is the same tried and trusted design of the BOSS SmartTouch® 2 controller, ensuring ease of operation during the longest winter events. The red center of the controller signifies D-Force capability, allowing for increased down force to be applied during backdragging for optimal scraping performance. Available only with D-Force capable Straight-Blade truck plow models including Super-Duty and HTX Straight-Blade plows. (Excludes EXT, Heavy-Duty and Trip-Edge plows.)



|                         |          |
|-------------------------|----------|
| D-FORCE CONTROLLER..... | STB10160 |
|-------------------------|----------|

## JOYSTICK CONTROL

If you prefer the feel of a joystick, opt for this versatile accessory, featuring a lighted on/off switch and right or left hand adjustment.

|                       |          |
|-----------------------|----------|
| STRAIGHT-BLADES ..... | STB03191 |
| V-PLOWS.....          | MSC03809 |



## SNOWPLOW SIGHT SYSTEM

Optional for all BOSS snowplows featuring the SmartLight™ 2 lighting system, our exclusive Snowplow Sight System allows you to align your truck and plow from inside your cab for hookups on the first try, every time. This system makes the fastest plow attachment system even faster and easier. Not compatible with SL3 with Ice Shield Technology.™



|                             |          |
|-----------------------------|----------|
| SNOWPLOW SIGHT SYSTEM ..... | MSC09644 |
|-----------------------------|----------|

## ATTACHMENT SYSTEMS



Attach your plow in just three easy steps with the industry's easiest to use snowplow attachment system.

|                    |          |
|--------------------|----------|
| SMARTHITCH® 2..... | MSC04679 |
|--------------------|----------|

## BLADE ENHANCEMENT

### PLOW WINGS

Increasing your blade width by a full 22" at a 30-degree angle, these convenient poly plow wings will cut your plowing time and attach and detach within seconds (excludes HTX and Heavy-Duty plows).

|                        |           |
|------------------------|-----------|
| STRAIGHT-BLADE .....   | MSC08042C |
| XT AND DXT PLOWS ..... | MSC08063B |

(Excludes HTX plows & Heavy-Duty plows. The only DXT models recommended for plow wing extensions are the 8'2" Steel DXT and 8'2" Poly DXT. Wing extensions do fit other DXT sizes and do not void the warranty but are not recommended, as the blade may sag when in the scoop position, due to the weight of the wing extensions.)



### HIGH-PERFORMANCE V-PLOW CUTTING EDGE

Featuring built-in curb guards and patented snow catcher, our patented V-plow cutting edge is made of Hardox® that delivers extended wear resistance compared to conventional cutting edges.

|                              |          |
|------------------------------|----------|
| 7'6" DRIVER SIDE .....       | BAL08857 |
| 7'6" PASSENGER SIDE .....    | BAR08856 |
| 8'2" DRIVER SIDE .....       | BAL08859 |
| 8'2" PASSENGER SIDE .....    | BAR08858 |
| 8'2" DXT DRIVER SIDE.....    | BAL18150 |
| 8'2" DXT PASSENGER SIDE..... | BAR18145 |
| 9'2" DRIVER SIDE .....       | BAL08861 |
| 9'2" PASSENGER SIDE .....    | BAR08860 |
| 9'2" DXT DRIVER SIDE.....    | BAL18165 |
| 9'2" DXT PASSENGER SIDE..... | BAR18155 |
| 10' DXT DRIVER SIDE.....     | BAL17580 |
| 10' DXT PASSENGER SIDE ..... | BAR17590 |



### CURB GUARDS

Protect the edges of your plow with these long-lasting, high-impact curb guards. Fits all BOSS Straight-Blade snowplow models (except HTX and Sport-Duty).

|   |          |
|---|----------|
| STRAIGHT-BLADE DRIVER SIDE.....               | STB03395 |
| STRAIGHT-BLADE PASSENGER SIDE.....            | STB03394 |
| STRAIGHT-BLADE HEAVY-DUTY DRIVER SIDE.....    | STB04364 |
| STRAIGHT-BLADE HEAVY-DUTY PASSENGER SIDE..... | STB04363 |

### D-FORCE

D-Force maintains consistent hydraulic down force through the use of a hydraulic accumulator to improve scraping performance while backdragging. D-Force is an optional accessory on new truck plow purchases. Available for select Straight-Blade truck plow models including Super-Duty and HTX Straight-Blade plows. (Excludes EXT, Heavy-Duty and Trip-Edge plows.)



|                                   |          |
|-----------------------------------|----------|
| SUPER-DUTY D-FORCE PLOW BOX ..... | STB15025 |
| HTX D-FORCE PLOW BOX .....        | STB15035 |

(D-Force needs to be purchased at the same time as a new plow. You are not able to add D-Force to your plow after purchase.)

### BACKDRAG EDGE

Improved scraping performance when backdragging. Available accessory on all Straight-Blade plows (excludes: 10' Heavy-Duty and EXT).

|                         |          |
|-------------------------|----------|
| 7'0" BACKDRAG EDGE..... | STB06534 |
| 7'6" BACKDRAG EDGE..... | STB06535 |
| 8'0" BACKDRAG EDGE..... | STB06536 |
| 8'6" BACKDRAG EDGE..... | STB06537 |
| 9'0" BACKDRAG EDGE..... | STB06538 |



### RUBBER SNOW DEFLECTOR

For increased visibility and safety, keep snow from blowing onto your windshield with a rugged snow deflector specifically designed for BOSS snowplows.

|  |           |
|--|-----------|
| 7' AND 7'6" HTX AND 7'6" STANDARD-DUTY<br>STRAIGHT-BLADE PLOWS .....     | MSC04587B |
| 7'6"-9'2" V-PLOWS AND 7'6"-9'0" SUPER-DUTY<br>STRAIGHT-BLADE PLOWS ..... | MSC01565  |
| 10' DXT, EXT AND HEAVY-DUTY<br>STRAIGHT-BLADE PLOWS .....                | MSC17611B |
| HEAVY-DUTY 9'0" .....  | MSC01565  |



BLADE ENHANCEMENT

URETHANE CUTTING EDGE

BOSS now offers a full line of Urethane Cutting Edges to cover our entire line of Straight-Blade plows. Ranging from 7’ all the way up to 10’, the edges offer between 1" to 2" of material thickness based on blade application and are reversible with a built-in bevel for optimum scraping performance. All necessary mounting hardware is included in the kit.

|  |          |
|--|----------|
| 7' X 6" X 1" HTX/SPORT-DUTY STRAIGHT-BLADE (7')          | STB09231 |
| 7'6" X 6" X 1" HTX/SPORT-DUTY STRAIGHT-BLADE (7'6")      | STB09232 |
| 7'6" X 8" X 1½" STD AND SUPER-DUTY STRAIGHT-BLADE (7'6") | STB09233 |
| 8' X 8" X 1½" SUPER-DUTY STRAIGHT-BLADE (8')             | STB09234 |
| 8'6" X 8" X 1½" SUPER-DUTY STRAIGHT-BLADE (8'6")         | STB09235 |
| 9' X 8" X 1½" SUPER-DUTY STRAIGHT-BLADE (9')             | STB09236 |
| 10' X 8" X 2" HEAVY-DUTY STRAIGHT-BLADE (10')            | STB09237 |



STABILITY & PERFORMANCE



REPLACEMENT BUMPER TRIM KIT

This kit eliminates the need to cut or modify a portion of the OEM bumper to access the push beam’s hooks. The kits utilize the factory mounting holes and give the plow vehicle an attractive, finished OEM look when installed. If the truck is going to be sold, the original bumper piece can be reinstalled to look like new.

|   |          |
|---|----------|
| BUMPER TRIM KIT, 2014-2015 CHEVY 1500   | MSC09409 |
| BUMPER TRIM KIT, 2015 + CHEVY 2500/3500 | MSC09279 |
| BUMPER TRIM KIT, 2014-2015 GMC 1500     | MSC09290 |
| BUMPER TRIM KIT, 2015 + GMC 2500/3500   | MSC09295 |
| BUMPER TRIM KIT, 2016 + GMC 1500        | MSC18870 |
| BUMPER TRIM KIT, 2016 + CHEVY 1500      | MSC18880 |

LIGHTING OPTIONS



30

SL3 WITH ICE SHIELD TECHNOLOGY™

|                                  |          |
|----------------------------------|----------|
| SL3 UPGRADE KIT                  | MSC16200 |
| SMARTLIGHT™ 1 TO SL3 UPGRADE KIT | MSC18860 |
| SMARTLIGHT™ 2 TO SL3 UPGRADE KIT | MSC19050 |

MAINTENANCE



TOUCH-UP PAINT

Cover chips and scrapes the professional way with BOSS touch-up paint.

|                    |          |
|--------------------|----------|
| RED, SPRAY PAINT   | MSC04098 |
| BLACK, SPRAY PAINT | MSC04036 |
| RED, QUART         | MSC04358 |

HIGH-PERFORMANCE HYDRAULIC FLUID

This specially formulated hydraulic fluid maintains its viscosity from normal use to temperatures as low as -40°F.

|        |          |
|--------|----------|
| GALLON | HYD01836 |
| QUART  | HYD01835 |

SHOVELS

SNOWPLOW SNOW  
PUSHER SHOVEL

BOSS has joined forces with the leader in high-performance, contractor-grade snow shovels! This tough, durable, high-performance shovel is built for the abuse of the season with premium blade material for unmatched scraping ability. Available in 28", 36" and 48" blade sizes. See your local BOSS Dealer for purchase.



EMERGENCY PARTS KITS

These kits feature the most useful replacement parts, packaged in a convenient soft-sided case that fits easily behind the seat of your truck (excludes 10' DXT, EXT and Heavy-Duty Straight-Blades).

|                                    |          |
|------------------------------------|----------|
| V-PLOW EMERGENCY PARTS KIT         | MSC04298 |
| STRAIGHT-BLADE EMERGENCY PARTS KIT | STB16187 |

PLOW TERMINAL CLEANER KIT

The BOSS Terminal Cleaner Kit cleans and restores male and female electrical plow connectors. It includes 0.188" male/female terminal cleaner, 0.25" male/female terminal cleaner and leather-type holster.


|                           |          |
|---------------------------|----------|
| PLOW TERMINAL CLEANER KIT | MSC05220 |
|---------------------------|----------|

SMARTLOCK® CYLINDERS

Keep your V-plow locked securely in the straight position while backdragging, with these easy to install locking cylinders.



|  |          |
|--|----------|
| PRE-2006 V-PLOWS                           | HYD07130 |
| 2006 & NEWER V-PLOWS                       | HYD09733 |
| 2006 & NEWER 10' V-PLOWS AND 10' DXT PLOWS | HYD09386 |



V-Blade Caster Wheel Kit\*\*

CASTER WHEELS

Ideal for moving your plow around in the garage or service bay, these wheels utilize existing shoe holders on the blade and make moving the plow a breeze. These heavy-duty wheels feature steel ball bearings for smooth movement and long-lasting life. Separate kits are available for straight-blades and V-plows. **Excludes:** Trip-Edge Straight-Blade, 10' DXT and Heavy-Duty Straight-Blade plows.

|                                   |          |
|-----------------------------------|----------|
| CASTER KIT, STRAIGHT-BLADE        | MSC09215 |
| CASTER KIT, V-PLOW (INCLUDES XT)  | MSC09216 |
| CASTER KIT, HTX (COVERS 7', 7'6") | MSC09249 |
| CASTER KIT, DXT                   | MSC01141 |
| CASTER KIT, HTX-V                 | MSC09235 |

\*\*Wheel color may vary.



Trip-Edge Shoe Kit



31

CAST-IRON PLOW SHOES

These ultra-rugged cast-iron shoes deliver extended wear resistance compared to conventional steel shoes.

|   |          |
|---|----------|
| PLOW SHOE ASSEMBLY*                               | MSC01570 |
| HTX PLOW SHOE BRACKET OPTION KIT (SHOES INCLUDED) | MSC09588 |
| TRIP-EDGE PLOW SHOE ASSEMBLY                      | TRP07880 |
| DXT SHOE KIT (BRACKET NOT INCLUDED)               | MSC18207 |
| DXT PLOW SHOE BRACKET OPTION KIT (SHOES INCLUDED) | MSC18184 |

\*DXT and HTX blades now include Plow Shoe Brackets as standard. Shoes sold separately.




BALLAST RETAINER KIT

Use the ballast retainer kit to hold sandbags securely in place in order to provide enhanced performance.

|                      |          |
|----------------------|----------|
| BALLAST RETAINER KIT | MSC09845 |
|----------------------|----------|




# MATERIALS GUIDE



32

# BOSS SNOWPLOW AUTHORIZED ACCESSORIES

|   |          |
|---|----------|
|  |          |
| <b>PRE-WET SYSTEM</b><br>Equipped with a 60-gallon tank and mounting bracket.       |          |
| PRE-WET SYSTEM.....   | MSC20100 |
| <b>LIGHT KIT</b>  |          |
| LIGHT KIT, FORGE 2.0.....   | MSC19525 |
| <b>TARP</b>   |          |
| TARP, FORGE 2.0.....  | VBS17190 |
| <b>INVERTED V</b><br>(Optional on pintle, standard on auger systems.)               |          |
| INVERTED V, FORGE 2.0 .....   | VBS17180 |
| INVERTED V, VBX 6500.....   | VBS15140 |
| INVERTED V, VBX 8000 AND VBX 9000 .....   | VBS15320 |


|  |          |
|--|----------|
|   |          |
| <b>PRO-LID</b><br>Weather seal protects deicing material inside the BOSS Spreader. The easy open, ergonomic design allows operators to remain on the ground while opening cover doors. |          |
| VBX 6500 PRO-LID W/ HARDWARE.....  | VBS15125 |
| VBX 8000 PRO-LID W/ HARDWARE.....  | VBS15130 |
| VBX 9000 PRO-LID W/ HARDWARE.....  | VBS15135 |
| <b>VBX VIBRATOR KIT</b><br>For improved material flow and handling, consider the addition of the VBX Vibrator Kit. (Optional on pintle, standard on auger systems.)                    |          |
| SINGLE VBX, FORGE 2.0 VIBRATOR KIT.....  | VBS14465 |
| DOUBLE VBX VIBRATOR KIT .....  | VBS14466 |
| <b>TGS VIBRATOR KIT</b><br>For improved material flow and handling, consider the addition of the TGS Vibrator Kit.   |          |
| TGS VIBRATOR KIT .....   | TGS05960 |
| <b>MATERIAL SAVER SYSTEM</b>   |          |
| MATERIAL SAVER SYSTEM .....  | TGS11328 |

# WHAT YOU GET WHEN YOU BUY A BOSS PLOW\*



33

- 1



**+ BLADE**  
Steel, stainless, poly – whichever you choose, it's durable and reliable.
- 2



**+ SMARTLIGHT™ 3**  
SL3 100% LED lights with Ice Shield Technology™ to prevent snow and ice build-up.
- 3



**+ PUSH FRAME/COUPLER**  
The powerful reinforced steel framework behind your plow.
- 4




**+ UNDERCARRIAGE**  
Serves as the connection point from the plow to the truck.
- 5




**+ HYDRAULICS & CONTROLLER**  
An intuitive, easy-to-use system completely protected from the elements.
- 6



**+ ATTACHMENT SYSTEM**  
A three-step, fully hydraulic system for quick and easy attachment.
- 7



**+ CUTTING EDGE OR BASE ANGLE**  
A durable cutting edge designed for precision and performance. On DXT models, the base angle serves as a cutting edge until worn.
- 8



**+ WORLD-CLASS SUPPORT**  
From our dealer network and factory customer support to our Owners Group, BOSS is there to BACK YOU UP.

\*The above equipment applies to brand-new truck plow purchases that require all components.



PERSONAL-USE PLOWS

HTX V AND STRAIGHT-BLADES

VEHICLE APPLICATION: LIGHT-DUTY, 4WD, ½-TON TRUCKS AND SUVs

| SPECIFICATIONS             | 7'6" HTX V-Plow Steel                     | 7' Steel / Poly / Stainless HTX  | 7'6" Steel / Poly / Stainless HTX  |
|----------------------------|---|--|--|
| Blade Width (Straight)     | 90" (229 cm)                              | 84" (213 cm)   | 90" (229 cm)   |
| Plowing Width @ 30° Angle  | 78" (198 cm)                              | 73" (185 cm)   | 78" (198 cm)   |
| Blade Height               | 32" (81 cm) at end, 25" (63 cm) at center | 26" (66 cm)  | 26" (66 cm)  |
| Plowing Width (V position) | 81" (206 cm)                              | N/A  | N/A  |
| Plowing Width (Scoop)      | 74" (188 cm)                              | N/A  | N/A  |
| Blade Thickness            | 14-ga Steel                               | 14-ga (0.19 cm) Mild Steel / ¼" (0.6 cm) Poly / 14-ga (0.19 cm) Stainless Steel            | 14-ga (0.19 cm) Mild Steel / ¼" (0.6 cm) Poly / 14-ga (0.19 cm) Stainless Steel            |
| Cutting Edge               | ¾" x 6" (0.95 cm x 15 cm)                 | ¾" x 6" (0.95 cm x 15 cm)  | ¾" x 6" (0.95 cm x 15 cm)  |
| Reinforcement Ribs         | 6 vertical, 2 diagonal                    | 4 vertical, 2 diagonal   | 6 vertical, 2 diagonal   |
| Plow Shoes                 | Optional                                  | Optional   | Optional   |
| Trip Springs               | 2   | 2  | 2  |
| SmartLock Cylinders        | 1¼" x 8¼" (3 cm x 21 cm)                  | N/A  | N/A  |
| Angle Cylinders            | N/A                                       | 1½" x 6½" (4 cm x 17 cm)   | 1½" x 6½" (4 cm x 17 cm)   |
| Lift Cylinder              | 1¾" x 1½" x 10" (5 cm x 3 cm x 25 cm)     | 1¾" x 1½" x 10" (5 cm x 3 cm x 25 cm)  | 1¾" x 1½" x 10" (5 cm x 3 cm x 25 cm)  |
| Attachment System          | SmartHitch 2                              | SmartHitch 2   | SmartHitch 2   |
| Plow Weight*               | 490 lb <sup>a</sup> (222 kg)              | 393 lb <sup>a</sup> (178 kg) / 367 lb <sup>a</sup> (166 kg) / 393 lb <sup>a</sup> (178 kg) | 440 lb <sup>a</sup> (200 kg) / 416 lb <sup>a</sup> (188 kg) / 440 lb <sup>a</sup> (200 kg) |
| Plow Lights                | SL3 L.E.D. with Ice Shield Technology     | SL3 L.E.D. with Ice Shield Technology  | SL3 L.E.D. with Ice Shield Technology  |

\*Plow weight does not include vehicle mount weight. <sup>a</sup>Vehicle mount weight range: 45-75 lb (20-34 kg).

PROFESSIONAL-USE PLOWS



EXT

VEHICLE APPLICATION: 4WD, ¾ AND 1-TON TRUCKS

| SPECIFICATIONS            | EXT                                    |
|---------------------------|--|
| Blade Width (Retracted)   | 96" (244 cm)                           |
| Blade Width (Extended)    | 120" (305 cm)                          |
| Plowing Width @ 30° Angle | 83" (211 cm)-IN, 103" (262 cm)-OUT     |
| Blade Height              | 30" (76.2 cm)                          |
| Blade Thickness           | 11-ga Steel                            |
| Cutting Edge              | ½" (1.27 cm) AR450                     |
| Reinforcement Ribs        | 9 vertical                             |
| Plow Shoes                | Optional                               |
| Trip Springs              | 4                                      |
| Angle Cylinders           | 1½" x 10" (4 cm x 25 cm)               |
| Wing Cylinders            | 1½" x 1½" x 12¾" (4 cm x 3 cm x 32 cm) |
| Lift Cylinder             | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)   |
| Shock Absorber            | 1                                      |
| Attachment System         | SmartHitch 2                           |
| Plow Weight*              | 970 lb <sup>b</sup>                    |
| Plow Lights               | SL3 L.E.D. with Ice Shield Technology  |

\*Plow weight does not include vehicle mount weight. <sup>b</sup>Vehicle mount weight range: 75-105 lb (34-48 kg).



STANDARD-DUTY STRAIGHT-BLADE

VEHICLE APPLICATION: 4WD, ½ AND ¾-TON TRUCKS AND SUVs

| SPECIFICATIONS            | 7'6" Standard-Duty Steel              |
|---------------------------|---------------------------------------|
| Blade Width (Straight)    | 90" (229 cm)                          |
| Plowing Width @ 30° Angle | 78" (198 cm)                          |
| Blade Height              | 27½" (70 cm)                          |
| Blade Thickness           | 14-ga high-strength Steel             |
| Cutting Edge              | ¾" x 6" (1 cm x 15 cm)                |
| Reinforcement Ribs        | 7 vertical                            |
| Plow Shoes                | Cast iron                             |
| Trip Springs              | 3                                     |
| Angle Cylinders           | 1½" x 10" (4 cm x 25 cm)              |
| Lift Cylinder             | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)  |
| Shock Absorber            | 1                                     |
| Attachment System         | SmartHitch 2                          |
| Plow Weight*              | 597 lb <sup>b</sup> (271 kg)          |
| Plow Lights               | SL3 L.E.D. with Ice Shield Technology |

\*Plow weight does not include vehicle mount weight. <sup>b</sup>Vehicle mount weight range: 75-105 lb (34-48 kg).



PROFESSIONAL-USE PLOWS

DXT

VEHICLE APPLICATION: 4WD, ¾ AND 1-TON TRUCKS AND SUVs, MEDIUM-DUTY TRUCKS 14,000-27,000 GVWR (10' ONLY)

| SPECIFICATIONS            | 8'2" Steel / Poly / Stainless DXT  | 9'2" Steel / Poly / Stainless DXT  | 10' Steel Heavy-Duty DXT                       |
|---------------------------|--|--|--|
| Blade Width (Straight)    | 98" (249 cm)   | 110" (279 cm)  | 120" (305 cm)                                  |
| Blade Width (V)           | 88" (224 cm)   | 99" (251 cm)   | 107" (272 cm)                                  |
| Blade Width (Scoop)       | 81" (206 cm)   | 92" (234 cm)   | 102" (259 cm)                                  |
| Plowing Width @ 30° Angle | 85" (216 cm)   | 95" (241 cm)   | 104" (264 cm)                                  |
| Blade Height              | 30" (76 cm) at center, 37½" (95 cm) at ends  | 30" (76 cm) at center, 37½" (95 cm) at ends  | 35" (88 cm) at center, 45" (114 cm) at ends    |
| Blade Thickness           | 11-ga Steel / ¾" Poly / 12-ga 304 Stainless Steel  | 11-ga Steel / ¾" Poly / 12-ga 304 Stainless Steel  | 11-ga Steel                                    |
| Base Angle                | ½" x 6" (1.3 cm x 15 cm)**   | ½" x 6" (1.3 cm x 15 cm)**   | ½" x 6" (1.3 cm x 15 cm)                       |
| Reinforcement Ribs        | 6 vertical, 2 diagonal   | 8 vertical, 2 diagonal   | 8 vertical, 2 diagonal                         |
| Plow Shoes                | Optional   | Optional   | Optional                                       |
| Trip Springs (Moldboard)  | 4 Extension Springs  | 4 Extension Springs  | 4 Extension Springs                            |
| Trip Springs (Base Angle) | 6 total  | 6 total  | 6 total  |
| SmartLock Cylinders       | 1½" x 10" (4 cm x 25 cm)   | 1½" x 10" (4 cm x 25 cm)   | 2" x 10" (5.08 cm x 25.4 cm)                   |
| Lift Cylinder             | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)   | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)   | 2¼" x 1½" x 12" (5.72 cm x 2.86 cm x 30.48 cm) |
| Attachment System         | SmartHitch 2   | SmartHitch 2   | SmartHitch 2                                   |
| Plow Weight*              | 868 lb <sup>b</sup> (394 kg) / 878 lb <sup>b</sup> (398 kg) / 920 lb <sup>b</sup> (417 kg) | 925 lb <sup>b</sup> (420 kg) / 935 lb <sup>b</sup> (424 kg) / 977 lb <sup>b</sup> (433 kg) | 1,205 lb <sup>b</sup> (547 kg)                 |
| Plow Lights               | SL3 L.E.D. with Ice Shield Technology  | SL3 L.E.D. with Ice Shield Technology  | SL3 L.E.D. with Ice Shield Technology          |

\*Plow weight does not include vehicle mount weight. <sup>b</sup>Vehicle mount weight range: 130-160 lb (59-73 kg).

\*\*The tripping base angles on the DXT come standard with curb guards and patented snow catcher, and they can be used as the cutting edge until worn. The optional cutting edge is made from Hardox® for maximum wear resistance and durability.

SUPER-DUTY STRAIGHT-BLADE

VEHICLE APPLICATION: 4WD, ½ TO 1-TON TRUCKS AND SUVs

| SPECIFICATIONS            | 7'6" Super-Duty Steel / Poly                                | 8' Super-Duty Steel / Poly                                  | 8'6" Super-Duty Steel                 | 9' Super-Duty Steel**                 |
|---------------------------|---|---|---------------------------------------|---------------------------------------|
| Blade Width (Straight)    | 90" (229 cm)  | 96" (244 cm)  | 102" (259 cm)                         | 108" (274 cm)                         |
| Plowing Width @ 30° Angle | 78" (198 cm)  | 83" (211 cm)  | 88" (224 cm)                          | 93½" (238 cm)                         |
| Blade Height              | 29" (74 cm)   | 29" (74 cm)   | 29" (74 cm)                           | 29" (74 cm)                           |
| Blade Thickness           | 11-ga Steel / ¾" (1 cm) Poly                                | 11-ga Steel / ¾" (1 cm) Poly                                | 11-ga Steel                           | 11-ga Steel                           |
| Cutting Edge              | ½" x 6" (1.3 cm x 15 cm)                                    | ½" x 6" (1.3 cm x 15 cm)                                    | ½" x 6" (1.3 cm x 15 cm)              | ½" x 6" (1.3 cm x 15 cm)              |
| Reinforcement Ribs        | 7 vertical, 2 diagonal                                      | 7 vertical, 2 diagonal                                      | 7 vertical, 2 diagonal                | 7 vertical, 2 diagonal                |
| Plow Shoes                | Cast iron   | Cast iron   | Cast iron                             | Cast iron                             |
| Trip Springs              | 4   | 4   | 4                                     | 4                                     |
| Angle Cylinders           | 1½" x 10" (4 cm x 25 cm)                                    | 1½" x 10" (4 cm x 25 cm)                                    | 1½" x 10" (4 cm x 25 cm)              | 1½" x 10" (4 cm x 25 cm)              |
| Lift Cylinder             | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)                        | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)                        | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)  | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)  |
| Shock Absorber            | 1   | 1   | 1                                     | 1                                     |
| Attachment System         | SmartHitch 2  | SmartHitch 2  | SmartHitch 2                          | SmartHitch 2                          |
| Plow Weight*              | 680 lb <sup>b</sup> (308 kg) / 706 lb <sup>b</sup> (320 kg) | 698 lb <sup>b</sup> (317 kg) / 722 lb <sup>b</sup> (328 kg) | 720 lb <sup>b</sup> (327 kg)          | 742 lb <sup>b</sup> (337 kg)          |
| Plow Lights               | SL3 L.E.D. with Ice Shield Technology                       | SL3 L.E.D. with Ice Shield Technology                       | SL3 L.E.D. with Ice Shield Technology | SL3 L.E.D. with Ice Shield Technology |

\*Plow weight does not include vehicle mount weight. <sup>b</sup>Vehicle mount weight range: 75-105 lb (34-48 kg). \*\*Includes 1-ton trucks with dual rear wheels.





# PROFESSIONAL-USE PLOWS

**XT**  
VEHICLE APPLICATION: 4WD, ¾ AND 1-TON TRUCKS AND SUVs



| SPECIFICATIONS             | 7'6" XT Steel                             | 8'2" XT Steel / Poly  | 9'2" XT Steel / Poly**                                       |
|----------------------------|---|---|--|
| Blade Width (Straight)     | 90" (229 cm)                              | 98" (249 cm)  | 110" (279 cm)  |
| Plowing Width (V position) | 81" (206 cm)                              | 88" (224 cm)  | 99" (252 cm)   |
| Plowing Width (Scoop)      | 74" (188 cm)                              | 81" (206 cm)  | 92" (234 cm)   |
| Plowing Width @ 30° Angle  | 77" (196 cm)                              | 85" (216 cm)  | 95" (241 cm)   |
| Blade Height               | 36" (91 cm) at end, 30" (76 cm) at center | 37" (94 cm) at end, 30" (76 cm) at center                   | 38" (96.52 cm) at end, 30" (76 cm) at center                 |
| Blade Thickness            | 14-ga Steel                               | 11-ga Steel / ¾" (1 cm) Poly                                | 11-ga Steel / ¾" (1 cm) Poly                                 |
| Cutting Edge (AR450)       | ½" x 6" (1.3 cm x 15 cm)                  | ½" x 6" (1.3 cm x 15 cm)                                    | ½" x 6" (1.3 cm x 15 cm)                                     |
| Reinforcement Ribs         | 6 vertical, 2 diagonal                    | 6 vertical, 2 diagonal                                      | 8 vertical, 2 diagonal                                       |
| Plow Shoes                 | Optional                                  | Optional  | Optional   |
| Trip Springs               | 4   | 4   | 4  |
| SmartLock Cylinders        | 1½" x 10" (4 cm x 25 cm)                  | 1½" x 10" (4 cm x 25 cm)                                    | 1½" x 10" (4 cm x 25 cm)                                     |
| Lift Cylinder              | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)      | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)                        | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)                         |
| Attachment System          | SmartHitch 2                              | SmartHitch 2  | SmartHitch 2   |
| Plow Weight*               | 713 lb <sup>a</sup> (323 kg)              | 785 lb <sup>a</sup> (356 kg) / 795 lb <sup>a</sup> (361 kg) | 842 lb <sup>a</sup> (382 kg) / 852 lb <sup>a</sup> (387 kg)) |
| Plow Lights                | SL3 L.E.D. with Ice Shield Technology     | SL3 L.E.D. with Ice Shield Technology                       | SL3 L.E.D. with Ice Shield Technology                        |

\*Plow weight does not include vehicle mount weight. <sup>a</sup>Vehicle mount weight range: 75-105 lb (34-48 kg). \*\*Includes 1-ton trucks with dual rear wheels.

**TRIP-EDGE SUPER-DUTY STRAIGHT-BLADE**  
VEHICLE APPLICATION: ½ TO 1-TON TRUCKS AND SUVs




| SPECIFICATIONS            | 7'6" Trip-Edge Steel                  | 8' Trip-Edge Steel / Stainless                              | 9' Trip-Edge Steel** / Stainless                            |
|---------------------------|---------------------------------------|---|---|
| Blade Width (Straight)    | 90" (229 cm)                          | 96" (244 cm)  | 108" (274 cm)   |
| Plowing Width @ 30° Angle | 78" (198 cm)                          | 83" (211 cm)  | 93½" (238 cm)   |
| Blade Height              | 31" (79 cm)                           | 31" (79 cm)   | 31" (79 cm)   |
| Blade Thickness           | 11-ga Steel                           | 11-ga Steel / 14-ga 304 Stainless                           | 11-ga Steel / 14-ga 304 Stainless                           |
| Base Angle                | ½" x 3½" (1.3 cm x 9 cm)              | ½" x 3½" (1.3 cm x 9 cm)                                    | ½" x 3½" (1.3 cm x 9 cm)                                    |
| Cutting Edge              | ½" x 6" (1.3 cm x 15 cm)              | ½" x 6" (1.3 cm x 15 cm)                                    | ½" x 6" (1.3 cm x 15 cm)                                    |
| Reinforcement Ribs        | 6 vertical, 2 diagonal                | 6 vertical, 2 diagonal                                      | 8 vertical, 2 diagonal                                      |
| Plow Shoes                | Cast iron                             | Cast iron   | Cast iron   |
| Trip Springs              | 4                                     | 4   | 4   |
| Trip Pivot Pin Diameter   | 1" (3 cm)                             | 1" (3 cm)   | 1" (3 cm)   |
| Trip Spring Type          | ¾" (1 cm) hooked extension spring     | ¾" (1 cm) hooked extension spring                           | ¾" (1 cm) hooked extension spring                           |
| Trip-Edge Adjustable      | Standard                              | Standard  | Standard  |
| Angle Cylinders           | 1½" x 10" (4 cm x 25 cm)              | 1½" x 10" (4 cm x 25 cm)                                    | 1½" x 10" (4 cm x 25 cm)                                    |
| Lift Cylinder             | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)  | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)                        | 2" x 1½" x 10" (5 cm x 3 cm x 25 cm)                        |
| Attachment System         | SmartHitch 2                          | SmartHitch 2  | SmartHitch 2  |
| Plow Weight*              | 796 lb <sup>a</sup> (361 kg)          | 825 lb <sup>a</sup> (372 kg) / 875 lb <sup>a</sup> (397 kg) | 877 lb <sup>a</sup> (399 kg) / 934 lb <sup>a</sup> (424 kg) |
| Plow Lights               | SL3 L.E.D. with Ice Shield Technology | SL3 L.E.D. with Ice Shield Technology                       | SL3 L.E.D. with Ice Shield Technology                       |

\*Plow weight does not include vehicle mount weight. <sup>a</sup>Vehicle mount weight range: 75-105 lb (34-48 kg). \*\*Includes 1-ton trucks with dual rear wheels.

# HEAVY-DUTY PLOWS

**HEAVY-DUTY STRAIGHT-BLADE**  
10' DXT (SPECIFICATIONS LISTED ON PAGE 35)  
VEHICLE APPLICATION: MEDIUM-DUTY TRUCKS 14,000-27,000 GVWR



| SPECIFICATIONS            | 9' Heavy-Duty Straight-Blade          | 10' Heavy-Duty Straight-Blade         |
|---------------------------|---------------------------------------|---------------------------------------|
| Blade Width (Straight)    | 108" (274 cm)                         | 120" (305 cm)                         |
| Plowing Width @ 30° Angle | 94" (239 cm)                          | 104" (264 cm)                         |
| Blade Height              | 34½" (88 cm)                          | 34½" (88 cm)                          |
| Blade Thickness           | 7-ga Steel                            | 7-ga Steel                            |
| Cutting Edge              | ½" x 6" (1.3 cm x 15 cm)              | ½" x 6" (1.3 cm x 15 cm)              |
| Reinforcement Ribs        | 8 vertical, 2 diagonal                | 8 vertical, 2 diagonal                |
| Plow Shoes                | Cast iron                             | Cast iron                             |
| Trip Springs              | 6                                     | 6                                     |
| Angle Cylinders           | 2" x 10" (5 cm x 25 cm)               | 2" x 10" (5 cm x 25 cm)               |
| Lift Cylinder             | 2¼" x 1½" x 12" (6 cm x 3 cm x 31 cm) | 2¼" x 1½" x 12" (6 cm x 3 cm x 31 cm) |
| Shock Absorber            | 2                                     | 2                                     |
| Attachment System         | SmartHitch 2                          | SmartHitch 2                          |
| Plow Weight*              | 1,152 lb <sup>c</sup> (523 kg)        | 1,205 lb <sup>c</sup> (547 kg)        |
| Plow Lights               | SL3 L.E.D. with Ice Shield Technology | SL3 L.E.D. with Ice Shield Technology |

\*Plow weight does not include vehicle mount weight. <sup>c</sup>Vehicle mount weight range: 130-160 lb (59-73 kg).

# ICE CONTROL EQUIPMENT

**TGS TAILGATE SPREADERS**  
VEHICLE APPLICATION: SUVs AND ½ TO 1-TON TRUCKS



| SPECIFICATIONS             | TGS 300*   | TGS 600*  | TGS 800**  | TGS 1100*   |
|----------------------------|--|---|--|---|
| Hopper Design              | Low-profile  | Low-profile   | Low-profile  | Low-profile   |
| Hopper Construction        | Polyethylene   | Polyethylene  | Polyethylene   | Polyethylene  |
| Hopper Capacity            | 3 cu ft / 200 lb (0.08 cu m / 91 kg)                                 | 6 cu ft / 400 lb (0.17 cu m / 181 kg)                             | 8 cu ft / 780 lb (0.23 cu m / 354 kg)                    | 11 cu ft / 800 lb (0.31 cu m / 363 kg)                            |
| Hopper Dimensions          | 21¼"H x 29"W x 15"D (53 cm x 74 cm x 38 cm)                          | 25¾"H x 38"W x 21"D (65 cm x 97 cm x 53 cm)                       | 48"H x 36"W x 21"D (122 cm x 91 cm x 53 cm)              | 34"H x 44"W x 24"D (86 cm x 112 cm x 61 cm)                       |
| Spreader Weight            | 70 lb (31 kg) plus mount   | 101 lb (45 kg) plus mount   | 220 lb (100 kg) plus mount                               | 152 lb (69 kg) plus mount   |
| Hopper Cover               | Solid poly   | Solid poly  | Solid poly   | Solid poly  |
| Feed Mechanism             | Internal auger w/material saving brush and adjustable drop-feed gate | Internal auger with cable-link agitator and adjustable feed gate  | Feed paddle  | Internal auger with cable-link agitator and adjustable feed gate  |
| Vibrator Kit               | Not recommended  | Optional  | Optional   | Optional  |
| Top Screen with Bag Opener | Top Screen Only  | Standard  | Standard   | Standard  |
| Motor                      | High-torque / 12-volt DC   | High-torque / 12-volt DC  | High-torque / 12-volt DC                                 | High-torque / 12-volt DC  |
| Spinner                    | 12" (31 cm) Poly   | 12" (31 cm) Poly  | 12" (31 cm) Poly   | 12" (31 cm) Poly  |
| Spread Width               | 4 - 30 feet (1 - 9 meters)   | 4 - 30 feet (1 - 9 meters)  | 4 - 20 feet (1 - 6 meters)                               | 4 - 30 feet (1 - 9 meters)  |
| Material Deflector         | Adjustable poly deflector  | Adjustable poly deflector   | Adjustable poly deflector                                | Adjustable poly deflector   |
| Receiver Class Hitch       | Class 2-4  | Class 3 or 4  | Class 4  | Class 4   |
| Control                    | Variable speed control with blast feature and overload protection    | Variable speed control with blast feature and overload protection | Independent controls for material feed and spinner speed | Variable speed control with blast feature and overload protection |
| Vehicle Applications       | SUV, light truck and up  | ¾ and 1-ton trucks  | ¾ and 1-ton trucks                                       | ¾ and 1-ton trucks  |

\*Designed to spread dry, free-flowing material (i.e., salt, deicers, etc.). \*\*Designed to spread sand, salt or a combination of both. See Spreader Materials Guide on Page 32 for more details on material spreading options.



ICE CONTROL EQUIPMENT

FORGE AND VBX HOPPER SPREADERS

VEHICLE APPLICATION: ¾, 1-TON, DUMP BODY AND FLATBED TRUCKS

| SPECIFICATIONS               | FORGE 2.0 AUGER / PINTLE CHAIN   | VBX 6500 AUGER / PINTLE CHAIN  | VBX 8000 AUGER / PINTLE CHAIN  | VBX 9000 AUGER / PINTLE CHAIN  |
|------------------------------|--|--|--|--|
| Hopper Capacity              | 2 cu yd (1.53 cu m)  | 1.5 cu yd (1.15 cu m)  | 2 cu yd (1.53 cu m)  | 3 cu yd (2.29 cu m)  |
| Hopper Length                | 70" (177.8 cm)   | 78" (198.1 cm)   | 96" (244 cm)   | 107" (272 cm)  |
| Hopper Overall Length        | 98" (249 cm)   | 93½" (237.5 cm)  | 115" (292 cm)  | 126" (330 cm)  |
| Hopper Height                | 38" (96.5 cm)  | 38¾" (97 cm)   | 38" (97 cm)  | 49" (124.5 cm)   |
| Hopper Width                 | 48" (122 cm)   | 48¼" (122.6 cm)  | 48¼" (123 cm)  | 48" (122 cm)   |
| Complete Unit Weight (Empty) | 650 lb (295 kg) / 700 lb (318 kg)  | 550 lb (250 kg) / 600 lb (272 kg)  | 600 lb (272 kg) / 650 lb (295 kg)  | 700 lb (322 kg) / 760 lb (345 kg)  |
| Hopper Construction          | 14 ga Stainless Steel  | ¾" (0.5 cm) Double Wall Polyethylene Hopper  | ¾" (0.5 cm) Double Wall Polyethylene Hopper  | ¾" (0.5 cm) Double Wall Polyethylene Hopper  |
| Spread Width                 | 2 ft - 40 ft (0.6 m - 12.2 m) Dry, free-flowing material                           | 2 ft - 40 ft (0.6 m - 12 m) Dry, free-flowing material                             | 2 ft - 40 ft (0.6 m - 12 m) Dry, free-flowing material                             | 2 ft - 40 ft (0.6 m - 12 m) Dry, free-flowing material                             |
| Max Feed Rate                | 2.3 cu ft (0.06 cu m) per minute / 4 cu ft (0.11 cu m) per minute                  | 2.3 cu ft (0.06 cu m) per minute / 4 cu ft (0.11 cu m) per minute                  | 2.3 cu ft (0.06 cu m) per minute / 4 cu ft (0.11 cu m) per minute                  | 2.3 cu ft (0.06 cu m) per minute / 4 cu ft (0.11 cu m) per minute                  |
| Lighting                     | Optional   | Dual 55 watt halogen variable output worklights                                    | Dual 55 watt halogen variable output worklights                                    | Dual 55 watt halogen variable output worklights                                    |
| Cover                        | Optional   | VCP Tarp w/integral tie-downs  | VCP Tarp w/integral tie-downs  | VCP Tarp w/integral tie-downs  |
| Top Screen                   | Standard   | Standard   | Standard   | Standard   |
| Gearbox                      | Planetary Gearbox  | Planetary Gearbox  | Planetary Gearbox  | Planetary Gearbox  |
| Motor                        | ½ HP Motor   | ¾ HP SS Feed Motor   | ¾ HP SS Feed Motor   | ¾ HP SS Feed Motor   |
| Trough                       | Austinetic Stainless Steel   | Austinetic Stainless Steel   | Austinetic Stainless Steel   | Austinetic Stainless Steel   |
| Cab Controller               | Dual Variable Speed Controller   | LCD Display Controller   | LCD Display Controller   | LCD Display Controller   |
| Dual Variable Speed Control  | Standard   | Standard   | Standard   | Standard   |
| Variable Speed Vibrator      | N/A  | 2 Standard (Auger) / Optional (Pintle)   | 2 Standard (Auger) / Optional (Pintle)   | 2 Standard (Auger) / Optional (Pintle)   |
| Vibrator                     | 1 Standard (Auger) / Optional (Pintle)   | N/A  | N/A  | N/A  |
| Inverted V Baffle            | Standard / Optional  | Standard / Optional  | Standard / Optional  | Standard / Optional  |
| Feed System                  | 6" OD X 9" (15 cm x 23 cm) pitch full length auger / 14" (36 cm) wide Pintle Chain | 6" OD x 9" (15 cm x 23 cm) pitch full length auger / 14" (36 cm) wide Pintle Chain | 6" OD x 9" (15 cm x 23 cm) pitch full length auger / 14" (36 cm) wide Pintle Chain | 6" OD x 9" (15 cm x 23 cm) pitch full length auger / 14" (36 cm) wide Pintle Chain |
| LED CHMSL                    | Standard   | Standard   | Standard   | Standard   |
| Adjustable Deflector         | Standard   | Standard   | Standard   | Standard   |
| Spinner Assembly             | Easily removable, Swing Out  | Easily removable and height adjustable   | Easily removable and height adjustable   | Easily removable and height adjustable   |
| Hopper Tie-Down Kit          | Standard   | Standard   | Standard   | Standard   |
| Spinner                      | 14½" (36.8 cm) Diameter Urethane Spinner   | 14½" (36.8 cm) Diameter Urethane Spinner   | 14½" (36.8 cm) Diameter Urethane Spinner   | 14½" (36.8 cm) Diameter Urethane Spinner   |
| Spinner Gearmotor            | ⅓ HP Gearmotor (Located above spinner)   | ⅓ HP Spinner Gearmotor (Located above spinner)                                     | ⅓ HP Spinner Gearmotor (Located above spinner)                                     | ⅓ HP Spinner Gearmotor (Located above spinner)                                     |
| Minimum Bed Length           | 6'6" (198.1 cm)  | 5'6" (167.6 cm)  | 6'6" (198.1 cm)  | 8' (243.8 cm)  |
| GVWR                         | 10,000 lb (4,535 kg)   | 9,000 lb Gross Vehicle Weight Required   | 10,000 lb Gross Vehicle Weight Required  | 13,000 lb Gross Vehicle Weight Required  |

See Spreader Materials Guide on Page 32 for more details on material spreading options.

\*All images shown may include standard/optional equipment. Please consult your local BOSS Dealer for more information.

TWO-YEAR LIMITED WARRANTY

All BOSS Snowplows and equipment are guaranteed to be free from defects in material and workmanship for two full years from the date of purchase. Stop by any authorized BOSS Dealer to receive complete details on our two-year parts and labor warranty. Please visit bossplow.com for more details.

LEGAL STATEMENT

Vehicles intended to be equipped with a spreader and/or snowplow must comply with the vehicle manufacturers' specifications for equipment application. BOSS Products reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein. BOSS Products may be protected by one or more patents; please see bossplow.com for more details.

BOSS EXTENDED FAMILY

GIVING YOU EVERYTHING YOU NEED TO RESTORE ORDER



QUESTIONS? CHAT LIVE ONLINE.  
BOSSPLOW.COM



Ask your BOSS Dealer or visit bossplow.com to browse the full family of BOSS products, including Truck Equipment, ATV/UTV Equipment, Heavy Equipment, Ice Control Equipment, Accessories and more.

DON'T FORGET TO ASK ABOUT AVAILABLE FINANCING OPTIONS.

Ask your BOSS Dealer or visit bossplow.com for more details.